



SECTION A-A

02	10/29/15	ADDED DETACHABLE LIQUID LEVEL BRACKET.	J.N.																		
01	09/03/15	REMOVED LIQUID LEVEL BRACKET.	J.N.																		
REV	DATE	DESCRIPTION	DRFTR																		
CONFIDENTIALITY		UNLESS OTHERWISE NOTED																			
THIS DRAWING & THE INFORMATION CONTAINED THEREIN IS CONFIDENTIAL & PROPRIETARY TO HEATEFLEX CORPORATION AND MAY NOT BE TRACED, PHOTOGRAPHED, REPRODUCED IN ANY MANNER, NOR USED FOR ANY PURPOSE WHATSOEVER WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF HEATEFLEX CORPORATION.		DIMENSIONS & TOLERANCING ARE IN INCHES (Millimeters) & PER ANSI-Y14.5 & HEATEFLEX CORP. DRAFTING STANDARDS.																			
		<table border="1"> <tr> <td>DECIMALS:</td> <td>in</td> <td>mm</td> </tr> <tr> <td>.XX</td> <td>± 0.01</td> <td>± 0.25</td> </tr> <tr> <td>.XXX</td> <td>± 0.005</td> <td>± 0.127</td> </tr> <tr> <td>.XXXX</td> <td>± 0.0005</td> <td>± 0.0127</td> </tr> <tr> <td>X/XX</td> <td>± 1/32</td> <td></td> </tr> <tr> <td>∅</td> <td>± 0.5"</td> <td>± 0.5"</td> </tr> </table>		DECIMALS:	in	mm	.XX	± 0.01	± 0.25	.XXX	± 0.005	± 0.127	.XXXX	± 0.0005	± 0.0127	X/XX	± 1/32		∅	± 0.5"	± 0.5"
DECIMALS:	in	mm																			
.XX	± 0.01	± 0.25																			
.XXX	± 0.005	± 0.127																			
.XXXX	± 0.0005	± 0.0127																			
X/XX	± 1/32																				
∅	± 0.5"	± 0.5"																			
DRAWN BY: J. Nieves		DATE: 07/17/15	<table border="1"> <tr> <td>ENG/DSGN:</td> <td>DATE:</td> </tr> <tr> <td><i>[Signature]</i></td> <td>10/30/15</td> </tr> </table>	ENG/DSGN:	DATE:	<i>[Signature]</i>	10/30/15														
ENG/DSGN:	DATE:																				
<i>[Signature]</i>	10/30/15																				
DRAFTING QC: J.N.		DATE: 10/30/15	<table border="1"> <tr> <td>DWG. NO.:</td> <td>REV.</td> </tr> <tr> <td>VHH1-1-03-C-A03-P526</td> <td>02</td> </tr> </table>	DWG. NO.:	REV.	VHH1-1-03-C-A03-P526	02														
DWG. NO.:	REV.																				
VHH1-1-03-C-A03-P526	02																				
SHEET: 1 OF 1		SCALE: NONE	FILE: FLOW PATH-R02																		



TITLE:  
HEATER/EXCHANGER ASSY.,  
FLOW PATH (REPRESENTATIVE)  
3.0KW, 208VAC, 1-PH